


Distributed By




Caliber Industrial Supply
 5500 Tomken Rd, Unit #2
 Mississauga, ON L4W 2Z4
 www.caliberindustrial.com

Mississauga ---- 905.624.5524
 Toronto ----- 416.626.7151
 Toll Free ----- 1.800.465.5743
 sales@caliberindustrial.com

Heavy Duty



The Original



CAT Form AD/B - ASME B5.50 FACTORY CLEARANCE

Taper	Order No.	Type	Item Description	D1	D2	D3	L1	L2	L3	Depth	T* Nm/ft.lb	Weight kg	G 2.5 at rpm	CLEARANCE PRICE
40	332-6821 10	METRIC**	HG HD-20/CAT40	20	59	63	90	70.95	17	90	400-535	2	25 000	\$499.00
50	332-6821 20	Heavy Duty	HG HD-20/CAT50	20	59	63	68	48.95	17	68	400-535	3.6	14 000	\$699.00
40	332-6821 10-T	INCH*** Heavy Duty	HG HD-3/4"/CAT40	0.750	2.323	2.480	3.543	2.793	0.669	3.543	295-395	2	25 000	\$499.00
50	332-6821 20-T		HG HD-3/4"/CAT50	0.750	2.323	2.480	2.677	1.927	0.669	2.677	295-395	3.6	14 000	\$699.00
50	332-6821 30-T		HG HD-1"/CAT50	1.000	2.756	2.913	3.622	2.872	0.669	3.622	546-693	4.6	14 000	\$699.00
40	332-685530	METRIC**	HG-25/CAT40	25	35	59	93	73.95	34	56	480-710	1.7	25 000	\$399.00
50	332-685580	The Original	HG-20/CAT50	20	30	52	68	48.95	30	52	260-425	3	14 000	\$549.00

* T = Min. and Max. transmittable torque using a h6 cylindrical tool, full depth insert.

** Dimensions, mm

*** Dimensions, inch

Information:

- Runout accuracy ≤ 0.004 mm at $2.5 \times D1$ (max. 50 mm), ≤ 0.00016 inch at $2.5 \times D1$ (max. 1.969 inch)
- Tool shank h6 or h7 can be used
- Center thread, M12x1, for axial length adjustment screw (screw not included). Part no. S042
- Coolant through on all holders
- Bore for data carrier - available on request

Accessories:

Use preset Torque Wrench, 10 Nm, to ensure correct mounting of tools. Part no. 19052.

ETP HYDRO-GRIP HD can be used with reducing sleeves.



Special Available Until Supplies Last!