

DIGITAL CALIPERS (STANDARD TYPE)



DATA
OUTPUT



1108-150

Part No.	Range	Accuracy	Price (CAD)
1108-150	0-6"/0-150mm	±.0010"	66.25
1108-200	0-8"/0-200mm	±.0015"	91.39
1108-300	0-12"/0-300mm	±.0015"	159.90

- Non waterproof
- Resolution .0005"/0.01mm
- Buttons: on/off, zero, inch/mm
- Automatic power off, move the digital unit to turn on power
- Battery CR2032, data output
- Made of stainless steel
- Optional accessory: wireless transmitter part no. 7315-25 (receiver is needed), bluetooth transmitter part no. 7214-25, data output cable part no. 7302-21, accessory set for digital calipers (part no. 6144, only for range 0-150mm and 0-200mm), depth base attachment (part no. 6140)


WATERPROOF DIGITAL OUTSIDE MICROMETER (WITH DATA OUTPUT)

DATA
OUTPUT

IP65
WATERPROOF



- Resolution .00005"/0.001mm
- Button function: on/off, set, inch/mm, data transmit
- IP65 dust/waterproof
- Data output, automatic power off
- Carbide measuring faces
- Ratchet stop
- Supplied with spherical anvil
- Optional accessory: wireless transmitter part no. 7315-31 (receiver is needed), bluetooth transmitter part no. 7214-31, data output cable part no. 7302-31



3101-25E

Part No.	Range	Accuracy	Price (CAD)
3101-25E	0-1"/0-25mm	±.00010"	304.00

OUTSIDE MICROMETERS



3203-2A

- Graduation .0001"
- Carbide measuring faces
- Ratchet stop type
- Supplied with setting standards (except 0-1")

Individual

Part No.	Range	Accuracy	Price (CAD)
3203-1A	0-1"	.00015"	43.36
3203-2A	1-2"	.00015"	48.86

Set

Part No.	Range	Micrometers included	Packaging	Price (CAD)
3203-33A	0-3"	3203-1A, 3203-2A, 3203-3A	blow mould case	147.01
3203-66A	0-6"	3203-1A, 3203-2A, 3203-3A, 3203-4A, 3203-5A, 3203-6A	blow mould case	336.17
3203-1212A	0-12"	3203-1A, 3203-2A, 3203-3A, 3203-4A, 3203-5A, 3203-6A, 3203-7A, 3203-8A, 3203-9A, 3203-10A, 3203-11A, 3203-12A	aluminum box	1276.62

*Micrometers up to 6" are supplied with inspection certificate

DIGITAL INDICATORS (ADVANCED TYPE)




DATA
OUTPUT

- Meet ASME B89.1.10M-2001
- Resolution .00005"/0.001mm
- Hysteresis .00005"
- Reading in digital and analog
- Display can be rotated by 320°
- Button function: tolerance Go and No-Go display, data preset, measuring direction change, max./min./TIR measurement, inch/metric conversion, absolute/incremental measurement
- Keep preset data and tolerance data in memory after restart
- CR2032 battery, data output
- Automatic power off (time is adjustable)
- Optional accessory: wireless transmitter part no. 7315-50M (receiver is needed), bluetooth transmitter part no. 7214-50M, data output cable part no. 7302-40M, 7303-40M, backs, contact points



2103-10E



Part No.	Range	Accuracy	Maximum measuring force	Cap	Remark	Price (CAD)
2103-10E	.5"/12.7mm	±.00015"	.337lbf	can lift	lug back	402.03
2103-25E	1"/25.4mm	±.00015"	.495lbf	cannot lift	lug back	492.94
2103-50E	2"/50.8mm	±.00015"	.562lbf	cannot lift	lug back	788.61

DIAL CALIPERS



SHOCK
PROOF

- Dial indicator graduation .001"
- Shockproof dial indicator
- Made of stainless steel



1311-6

Part No.	Range	Accuracy	Dial face color	Price (CAD)
1311-6	0-6"	±.0015"	light green	91.75
1311-8	0-8"	±.0020"	light green	114.18
1311-12	0-12"	±.0020"	light green	178.03

DIGITAL HEIGHT GAUGE WITH DRIVING WHEEL



DATA
OUTPUT

- Non waterproof
- Resolution .0005"/0.01mm
- Buttons: on/off, zero, inch/mm, preset +, preset -, hold
- Automatic power off, move the digital unit to turn on power
- Carbide tipped scriber
- Made of stainless steel
- Battery CR2032, data output
- Supplied with dust cover
- With dial test indicator holder
- Optional accessory: wireless transmitter part no. 7315-22 (receiver is needed), bluetooth transmitter part no. 7214-22, data output cable part no. 7302-22, clamp for protractors (part no. 2372-CLAMP)

Part No.	Range	Accuracy	Price (CAD)
1156-300	0-12"/0-300mm	±.0015"	704.11



1156-300

UNIVERSAL MAGNETIC STAND

- For digital/dial indicators and dial test indicators
- Applicable holding stem: 3/8" DIA
- With fine adjustment and dovetail groove

Part No.	Magnetic force	Price (CAD)
6210-80E	176lbf	159.97

6210-80E



DIAL INDICATOR



- Graduation .001"
- Dial reading: 0-100
- Meet ASME B89.1.10M-2001
- With lug back
- Supplied with limit pointers and bezel clamp
- Optional accessory: backs, contact points

Part No.	Range	Accuracy	Price (CAD)
2307-1	1"	First 2.5 rev ±.001" Overall ±.002"	39.94



2307-1

WiFi DIGITAL MEASURING MICROSCOPE PART NO. ISM-WF200

stand (part no. ISM-WSTD, optional)

- Maximum working distance is 200" under WiFi mode
- Can be connected to multiple iPads, Android devices or computers at the same time under WiFi mode
- Take pictures and videos
- Supplied with software



SPECIFICATION

Price (CAD)	457.00
Magnification	10X~200X
Pixel	1.3M (resolution: 1280x1024)
Illumination	built-in adjustable LED
Power supply	built-in rechargeable battery

MAGNIFICATION, FOCUS DISTANCE, VIEW FIELD AND ACCURACY

Magnification	Focus distance	View field	Accuracy
50X	.83"	.32x.25"	1.2mil
100X	.51"	.15x.12"	0.6mil
150X	.63"	.10x.08"	0.4mil
200X	.75"	.07x.06"	0.3mil

Distributed by



Call: 905.624.5524

Email: sales@caliberindustrial.com