



INSIZE

MEASUREMENT SOLUTION PROVIDER



To Place Orders:



Call: 905.624.5524



Email: sales@caliberindustrial.com

DIGITAL CALIPERS (FRACTION READING)



DATA
OUTPUT

- Non waterproof
- Resolution: 1/128", 0.01mm, .0005"
- Buttons: unit (inch fraction/mm/inch), on/off, zero
- Automatic power off, move the digital unit to turn on power
- Battery CR2032, data output
- Data output (for mm and inch)
- Made of stainless steel
- wireless transmitter part no. 7315-25 (receiver is needed), accessory set for digital calipers (part no. 6144, only for range 0-6" and 0-8"), depth base attachment (part no. 6140)



1102-150

Part No.	Range	Accuracy	Price (CAD)
1102-150 *	0-6"/0-150mm	±.0010"	115.72
1102-200 *	0-8"/0-200mm	±.0015"	172.68
1102-300 *	0-12"/0-300mm	±.0015"	250.78

*Supplied with manufacturer inspection certificate

TUBULAR INSIDE MICROMETERS

- Accuracy: [.0003+.00005(L/2)]", L=maximum measuring length (inch)
- Optional accessory: setting ring (part no. 6313), gauge block accessory (part no. 6881), cylinder gauge block (part no. 4001), caliper/height gauge checker (part no. 6884)



3221-8

Part No.	Range	Travel of micrometer head	Extension rods	Graduation	Price (CAD)
3221-8	2-8"	.5"	6 pcs	.001"	282.64
3221-12	2-12"	.5"	10 pcs	.001"	308.41
3221-20	8-20"	1"	3 pcs	.001"	393.59
3221-40	8-40"	1"	8 pcs	.001"	1248.25

DIGITAL CHAMFER GAUGE

DATA
OUTPUT

- Non waterproof
- Measure 15°/20°/30°/45°/60° chamfer dimension
- Resolution .0005"/0.01mm
- Buttons: on/off, zero, inch/mm
- Automatic power off, move the digital unit to turn on power
- Data output
- Battery CR2032
- Made of stainless steel



1180-6

With data interface
(optional wireless transmitter part no. 7315-25, receiver is needed)

Part No.	Range	Accuracy	Chamfer (α)	Price (CAD)
1180-6	0-.39"/0-10mm	±.0025"	45°	250.66

DIAL INDICATOR



- Maximum measuring force: .405lbf
- Range/rev: .05"
- Meet ASME B89.1.10M-2001
- With lug back
- Supplied with limit pointers and bezel clamp
- Optional accessory: backs, contact points



2307-105

Part No.	Range	Graduation	Accuracy		Cap	Dial reading	Price (CAD)
			First 2,5 rev	Overall			
2307-105 *	1"	.0005"	±.0005"	±.002"	can lift	0-50	53.46

*Supplied with manufacturer inspection certificate

UNIVERSAL MAGNETIC STAND

- with fine adjustment and dovetail groove
- For digital/dial indicators and dial test indicators

POPULAR
MODEL



6210-80E

Part No.	Magnetic force	Applicable holding stem	Price (CAD)
6210-80E	176lbf	3/8" DIA	159.97

DIGITAL PROTRACTORS

- Resolution: 0.1°
- Buttons: on/off, zero
- With clamping screw to lock the blades
- Graduation of blade: 1mm and 1/32"
- Made of stainless steel
- CR2032 battery
- Automatic power off

Part No.	Size (L)	Range	Accuracy	Price (CAD)
2176-200	8"	0-360°	±0.3°	62.54
2176-300	12"	0-360°	±0.3°	71.85



2176-200

MACHINIST SQUARES WITH WIDE BASE (ECONOMIC TYPE)

ATTENTION: NO ANTI-RUST TREATMENT, NOT HARDENED

- DIN875 grade 2
- Made of carbon steel, no anti-rust treatment, not hardened



4707-100

Part No.	Size (L×W)	Squareness		Price (CAD)
		Inside (α)	Outside (β)	
4707-50	2.0×1.6"	.00094"	.00098"	22.57
4707-75	3.0×2.0"	.00102"	.00110"	23.02
4707-100	3.9×2.8"	.00110"	.00118"	34.17
4707-150	6×4"	.00130"	.00138"	46.80

PITCH GAUGES (LOW ACCURACY)

- Identify the pitch of screw thread
- Made of medium carbon steel



4820-122

Metric 60° screw		Quantity of leaves	Price (CAD)
Part No.	Range		
4820-122	0.4-7.0mm	22	15.48

Unified 60° screw		Quantity of leaves	Price (CAD)
Part No.	Range		
4820-230	4-42TPI	30	19.29

FILLET WELDING GAUGES

- Measure concave and convex weld sizes
- 7 blades are included
- Made of stainless steel



4836-2

4836-1

Part No.	Size	Accuracy	Price (CAD)
4836-2	1/8" (3.2mm), 3/16" (4.8mm), 1/4" (6.4mm), 5/16" (7.9mm), 3/8" (9.5mm), 7/16" (11.1mm), 1/2" (12.7mm), 5/8" (15.9mm), 3/4" (19.1mm), 7/8" (22.2mm), 1" (25.4mm)	±.02" (0.5mm)	57.23
4836-1	3, 4, 5, 6, 8, 9, 10, 11, 12, 14, 16, 19, 22, 25mm	±0.5mm	52.48

U.S. STANDARD SHEET METAL GAUGE

- For gaging sheet metal, plate iron and steel
- Hardened to HRC50-57



4809

Part No.	Range	Price (CAD)
4809	0-36 (.3125-.0070")	37.50

MAGNIFIERS WITH ILLUMINATION

- Glass lens
- Powered by 3×AAA batteries (included)



7513-2

7513-4

Part No.	Magnification	Lens diameter (D)	Price (CAD)
7513-2	2X	2.953" DIA	12.92
7513-4	4X	1.969" DIA	11.87